



- 精確度: $\pm 0.2\%$ R.O. (PT-100)
 $\pm 0.3\%$ R.O. (K)
- 元件等級: A class
- 反應速度: 15 sec
- 認證規範: DIN IEC 60751

規格特性

- ◆ Accuracy: $\pm 0.2\%$ R.O. (PT-100)
 $\pm 0.3\%$ R.O. (Thermocouple: K)
- ◆ Measuring Range: K: 0~1200°C
PT-100: -100~800°C
- ◆ Output Ripple: $\leq \pm 0.3\%$ R.O.
- ◆ Temperature Coefficient: 100ppm/°C (0~60°C)
- ◆ Operating Humidity: 20 to 90% RH (non-condensing)
- ◆ Storage Humidity: 20 to 90% RH (non-condensing)
- ◆ Input Impedence: Thermocouple: $\geq 1\text{M}\Omega$
PT-100: $\geq 10\text{M}\Omega$
- ◆ Material: Tube Thread: Steel 316
Head: Aluminum

選用型號規格

BTL - 代碼1 代碼2 - 代碼3 - 代碼4 代碼5 - N - NN - P

碼1	管徑	碼3	管長	碼4	接線長度
3	3.2 mm	02	20 mm	03	3 M
G	3.8 mm			10	10 M
碼2	輸入種類			碼5	接線材質
K	K Type			T	鐵氟龍線
P	RTD (PT-100)				

尺寸圖

